

EAC

5000



NVIDIA® Jetson AGX Orin™ Embedded AI Computing System




Automated Agricultural Machinery



- Advanced NVIDIA® Jetson AGX Orin™ platform delivers up to 275 TOPS AI performance
- The latest NVIDIA Ampere™ architecture, featuring with 2048 NVIDIA® CUDA® cores and 64 Tensor cores
- Supports 8 GMSL 1/2 automotive cameras with Fakra-Z connectors
- 1 PCIe Gen4 x8 expansion slot supports optional multiple 10GigE/PoE LAN/USB connections
- 2 Isolated CAN Bus support Flexible Data-rate, 2 COM RS-232/422/485
- 2 GigE LAN, 5 USB 3.1, 1 Digital Display supports 8K60
- Supports device remote management by Allxon
- DC 9V to 50V wide range power input, Ignition Power Control

Autonomous Mobile Robots



Real-Time Video Analytics



Vecow

Specifications

System

CPU	EAC-5000-R32 : 8-core Arm® Cortex®-A78AE v8.2 64-bit CPU EAC-5000-R64 : 12-core Arm® Cortex®-A78AE v8.2 64-bit CPU
GPU	EAC-5000-R32 : 1792-core NVIDIA Ampere™ architecture GPU with 56 Tensor Cores EAC-5000-R64 : 2048-core NVIDIA Ampere™ architecture GPU with 64 Tensor Cores
DL Accelerator	2x NVDLA Engines
Memory	EAC-5000-R32 : 1 32GB LPDDR5 DRAM EAC-5000-R64 : 1 64GB LPDDR5 DRAM
OS	Linux Ubuntu 20.04 with JetPack

I/O Interface

USB	- 1 USB 3.1 Gen 2, supports up to 10Gbps - 4 USB 3.1, support up to 5Gbps
Serial	2 COM RS-232/422/485
CAN Bus	2 Isolated CAN Bus support CAN FD
DIO	16 Isolated DIO (8 DI, 8 DO)
Micro USB	- 1 Micro USB console debug port - 1 Micro USB OS flash port
Button	- 1 Power Button - 1 Force Recovery Button - 1 Reset Button
LED	Power, SSD, 2 User Programmable
SIM	2 SIM Card Socket
Antenna	6 Antenna for WiFi/4G/5G/LTE/GPRS/UMTS

Expansion

PCIe	1 PCIe Gen4 x8 Slot
M.2	- 1 M.2 Key B Socket (3042/3052) - 1 M.2 Key E Socket (2230)

Graphics

Interface	1 Digital Display, up to 8K60
Video Encode	EAC-5000-R32 : 1x 4K @60, 3x 4K @30, 6x 1080p @60, 12x 1080p @30 (HEVC) EAC-5000-R64 : 2x 4K @60, 4x 4K @30, 8x 1080p @60, 16x 1080p @30 (HEVC)
Video Decode	EAC-5000-R32 : 1x 8K @30, 2x 4K @60, 4x 4K @30, 9x 1080p @60, 18x 1080p @30 (HEVC) EAC-5000-R64 : 1x 8K @30, 3x 4K @60, 7x 4K @30, 11x 1080p @60, 22x 1080p @30 (HEVC)

Camera

GMSL	8 Fakra-Z connectors for GMSL 1/2 automotive cameras
------	--

Storage

M.2	2 M.2 Key M Socket (2280)
eMMC	1 eMMC 5.1, 64GB
SD	1 Micro SD (External)

Ethernet

LAN 1 to LAN 2	10/100/1000 Base-T Ethernet GigE LAN, RJ45 Connector (Optional X-coded M12 Connector)
----------------	---

Power

Power Input	DC 9V to 50V
Power Interface	3-pin Terminal Block : V+, V-, Frame Ground
Ignition Control	16-mode Software Ignition Control
Remote Switch	3-pin Remote Switch Terminal Block
OOB Management	Remote Power On/Off and Remote Reset Control (Optional)

Mechanical

Dimensions	260 mm x 182 mm x 69 mm (10.23" x 7.16" x 2.72")
Weight	3.8 kg (8.39 lb)
Mounting	- Wallmount - DIN Rail and VESA Mount (Optional)

Environment

Operating Temp.	30W TDP Mode : -20°C to 70°C (-4°F to 158°F) MAXN TDP Mode : -20°C to 55°C (-4°F to 131°F)
Storage Temp.	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @70°C
Shock	Operating, MIL-STD-810G, Method 516.7, Procedure I
Vibration	Operating, MIL-STD-810G, Method 514.7, Procedure I, Category 4
EMC	CE, FCC, EN50155, EN50121-3-2

* All product information may subject to change without prior notice.

* The rights of all brand names, product names and trademarks belong to their respective owners.
Copyright © 2022 Vecow Co., Ltd. All rights reserved.

Order Information

Model Name	Platform	RAM	LAN	USB 3.1	Serial	Iso. CAN	Iso. DIO	PCIe Slot	GMSL	SIM	M.2
EAC-5000-R32	Jetson AGX Orin	32GB	2	5	2	2	16	1	8	2	4
EAC-5000-R64		64GB									

Accessories

PWA-160WB-WT	160W, 24V, 85V AC to 264V AC Power Adapter with 3-pin Terminal Block, Wide Temperature -30°C to +70°C
PWA-180WB	180W, 24V, 90V AC to 264V AC Power Adapter with 3-pin Terminal Block
PWA-280WB-WT	280W, 24V, 85V AC to 264V AC Power Adapter with 3-pin Terminal Block, Wide Temperature -30°C to +70°C
VESA Mount	VESA Mounting Kit
DIN-RAIL	DIN Rail and VESA Mounting Kit
GMSL Camera Kit	GMSL Camera with Fakra-Z connector
M.2 Storage Module	M.2 Key M/Key B PCIe Storage Module
5G Module	5G Module with Antenna
4G Module	4G/GPS Module with Antenna
WiFi & Bluetooth	WiFi & Bluetooth Module with Antenna
OOB Module	On-board Out-of-Band Management Module

Dimensions & Drawing

Unit : mm (inch)

